

# Marlow<sup>®</sup> DATASHEET

## 3 STRAND NELSON

A tough, no nonsense 3 strand rope manufactured using staple polypropylene fibres. High grip, abrasion resistance and lightweight, Nelson makes a great easily spliced general purpose rope.



### Key Specifications:

<b>Material:</b>	Polypropylene
<b>Lengths:</b>	100m, 200m, 220m
<b>Colour:</b>	White
<b>Properties:</b>	Hardwearing, lightweight and economical lowering rope Excellent grip Very easily spliced Good abrasion resistance

### PERFORMANCE

DIAMETER	WEIGHT	BREAK LOAD	MIN BREAK LOAD
mm	kg/100m	kg	kN
6	1.70	648	5.89
8	3.00	1145	10.40
10	4.50	1685	15.30
12	6.50	2387	21.68
14	9.00	3294	29.92
16	11.5	4072	36.98
18	14.8	5195	47.19
20	18.0	6264	56.90
24	26.0	8770	79.66
28	35.5	11556	104.97
32	46.0	14537	132.04

Marlow Ropes Ltd  
Ropemaker Park  
Hailsham  
East Sussex, BN27 3GU  
England

Marlow Ropes, Inc.  
Cordage Business Park  
Plymouth  
MA 02360  
USA

UK: +44 (0) 1323 444 444  
sales@marlowropes.com  
US: +1 508 830 444  
salesusa@marlowropes.com

[www.marlowropes.com](http://www.marlowropes.com)

#### Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.



Certificate Number 315  
ISO 9001  
ISO 14001