

# Marlow

## 3 STRAND POLYESTER

The classic 3 strand line, Marlow's 3 Strand is manufactured using the highest quality materials to produce a rope of the highest quality with the perfect flexibility and firmness. Polyester won't degrade in UV and remains supple and strong even when wet.



### Key Specifications:

<b>Applications:</b>	General purpose, Mooring
<b>Material:</b>	Polyester
<b>Construction:</b>	3 strand polyester
<b>Colours:</b>	White with black fleck, black and navy blue
<b>Properties:</b>	No strength loss when wet Soft and flexible, very easily spliced Good abrasion resistance Manufactured to BS EN ISO1141
<b>Lengths</b>	100m, 200m, 220m ( plain white only)

### PERFORMANCE

DIAMETER	WEIGHT	BREAK LOAD	MIN BREAK LOAD
mm	kg/100m	kg	kN
4	1.21	529	2.94
6	2.73	951	5.49
8	4.80	1465	10.01
10	7.85	2570	15.60
12	10.9	3170	22.27
14	14.9	3930	31.20
16	19.4	4766	39.83
18	24.6	6600	49.83
20	30.3	9230	62.29
24	46.0	11210	89.57
28	62.8	14640	119.98
32	82.0	18840	154.02

Marlow Ropes Ltd  
Ropemaker Park  
Hailsham  
East Sussex, BN27 3GU  
England

Marlow Ropes, Inc.  
Cordage Business Park  
Plymouth  
MA 02360  
USA

UK: +44 (0) 1323 444 444  
sales@marlowropes.com  
US: +1 508 830 444  
salesusa@marlowropes.com



[www.marlowropes.com](http://www.marlowropes.com)

Disclaimer  
Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

Certificate Number 315  
ISO 9001  
ISO 14001