

Marlow DATASHEET®

ACCESSORY CORDS

Marlow's range of accessory cords includes nylon, polyester and Dyneema® cords all certified to CE standards.

General Accessory Cord

Strong, light, polyamide (Nylon) accessory cord provides ideal performance for a variety of application.

5mm Dyneema® Accessory Cord

This CE certified, high strength Dyneema® accessory cord is ideal for rigging, where exceptional strength and light weight are essential. Very low elongation ensures accurate positioning to maintain efficient rigging.

8mm Viper 2 Accessory Cord

Viper 2 is CE certified, high strength cord incorporating the proven Viper Vectran and polyester cover technology and Vectran core.

9mm Accessory Cord

Marlow's low-stretch polyester rigging rope is ideal for any application where Nylon's elongation is undesirable.



PERFORMANCE

DIAMETER	WEIGHT	AVERAGE BREAK LOAD	MIN BREAK LOAD	TEST STANDARD
mm	g/m	kN	kg	
3	7	2.0	183	-
4	10.3	3.6	326	EN564
5	14.2	5.6	510	EN564
6	22.7	8.0	734	EN564
7	30.0	10.9	999	-
8	37.9	14.2	1305	EN564

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com

www.marlowropes.com

Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.



Certificate Number 315
ISO 9001
ISO 14001