


Marlow ^{DATASHEET} [®]

DYNAMIC CLIMBING ROPES

A combination of good handling, abrasion resistance and outstanding dynamic and energy absorption performance make Marlow Dynamic Climbing Ropes ideal for Cows Tails, climbing and safety and back up lines when abseiling or work positioning.



APPLICATIONS

Climbing, safety line, back up line, fall arrest, Cows Tails

MATERIAL

MANUFACTURED FROM POLYAMIDE (NYLON): High elongation (gives good energy absorption)
Good abrasion resistance
Outstanding energy absorption

CONSTRUCTION

40 OR 48 PLAIT BRAIDED COVER:

Abrasion resistant
Flexible and easily handled
Zero sheath slippage

MULTIPLE TWISTED CORES:

High energy absorption
Torque balanced - no twisting

PERFORMANCE

SINGLE ROPES	10.5mm	11mm
Rope Type	Single	Single
Weight (g/m)	70	78
Sheath Protection	34%	31%
No. drops	7	11
Impact Force	8kN	8kN
Dynamic Elongation	35%	35%
Static Extension	8%	8%
Sheath Slippage	0	0
Certification	EN 892	EN 892

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com



www.marlowropes.com

Disclaimer
Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

Certificate Number 315
ISO 9001
ISO 14001