DATASHEET (R)

MAVERICK

Maverick is the new generation of smaller diameter climbing lines from Marlow Ropes that offers outstanding dynamic performance thanks to its nylon core and friction-resistant polyester cover.

The revolutionary 11.5mm diameter offers lighter weight and flexibility, performing extremely well with modern hardware climbing devices, offering a smoother climb overall. CE and EN1891 Type A certified, available with a low-profile spliced eye finished with a whip.

REVOLUTIONISING MODERN CLIMBING

ROPE PROPERTIES	MEASUREMENT
DIAMETER	11.5 mm
WEIGHT	93 g/m
CORE WEIGHT	44.7 g/m
COVER WEIGHT	48.3 g/m
ELONGATION	*2.5%
STATIC STRENGTH	35.0 kN
STRENGTH FIG 8	18.8 kN
STRENGTH SPLICED	22.9 kN
IMPACT FORCE	5.2 kN
DROPS	7+ (req. 5+)

*Elongation from 50kg to 150kg load, as tested according to EN 1891



Key Specifications:

Material: Lengths: Colour: Features:

Terminations:

Nylon core and Polyester cover Hi-Vis Lime/Orange and Lime/Green Light weight and performs well with all modern climbing hardware devices. Low profile splice finished with a whip

Marlow Ropes Ltd Ropemaker Park Hailsham East Sussex, BN27 3GU England

Marlow Ropes, Inc. Cordage Business Park Plymouth MA 02360 USA

UK: +44 (0) 1323 444 444 sales@marlowropes.com US: +1 508 830 444 salesusa@marlowropes.com



ISO 1400

www.marlowropes.com

narufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied Mar cluding the implied warranties of merchantability and fitness for a particular purpose Marlow Ropes Ltd shall not be liable for any se guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes with