

# Marlow<sup>®</sup> DATASHEET

## PS12

PS12 is a soft, yet strong 12 strand Polyester rope which has been designed to be easily spliced for halyard tails and lazy jacks.



### Key Specifications:

<b>Material:</b>	High Tenacity Polyester
<b>Construction:</b>	12 strand Braided
<b>Properties:</b>	Flexible and easily spliced Excellent stability improves 'feel' Good general purposed line

### PERFORMANCE

DIAMETER		CIRCUMFERENCE		MASS		AVERAGE STRENGTH			MIN STRENGTH		
mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg	lb	kN		
4	5/32	11.9	0.97	678	1492	6.7	610	1342	6.0		
5	3/16	19.1	1.26	1060	2332	10.4	954	2099	9.4		
6	7/32	24.7	1.74	1331	2928	13.1	1198	2635	11.8		

Marlow Ropes Ltd  
Ropemaker Park  
Hailsham  
East Sussex, BN27 3GU  
England  
[www.marlowropes.com](http://www.marlowropes.com)

Marlow Ropes, Inc.  
Cordage Business Park  
Plymouth  
MA 02360  
USA

UK: +44 (0) 1323 444 444  
[sales@marlowropes.com](mailto:sales@marlowropes.com)  
US: +1 508 830 444  
[salesusa@marlowropes.com](mailto:salesusa@marlowropes.com)



**Disclaimer**  
Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

**Certificate Number 315**  
ISO 9001  
ISO 14001