

Marlow

RHINO SLING - LIFTING & RECOVERY

High strength | Light weight | Improved D:d ratios | Flexible | Hard wearing | Dyneema® SK78/SK75



Manufactured using our high strength pre-stretched D12* with our ChafeGuard Dyneema cover. The construction of this sling results in very high strength and low weight, providing easy handling and allowing safe and quick installation and change overs.

The design of the Rhino Sling allows for much shorter lengths and improved D:d ratios in the spliced eyes when compared to traditional constructions.

Super low stretch thanks to the pre-stretched D12* strength member, the multi-use Rhino Sling is suitable for all lifting and recovery operations.

* for slings up to 120mt D12+ used on larger slings

** custom sizes available



WHITE RHINO SLING



STRENGTH RATING (mt) (MBL)		WLL(mt): Lifting (7:1)		WLL (mt): Towing (2:1)		DIAMETER		MINIMUM LENGTH**		SUGGESTED LENGTH**		WEIGHT		EYE SIZE	
tonnes	lbs	tonnes	lbs	tonnes	lbs	mm	inch	m	inch	m	feet	kg	lbs	mm	inch
10	22000	1.43	3150	5.00	11000	16	5/8	0.30	12	1.5	5	0.20	0.44	250	10
10	22000	1.43	3150	5.00	11000	16	5/8	0.30	12	3	10	0.40	0.89	250	10
10	22000	1.43	3150	5.00	11000	16	5/8	0.30	12	6	20	0.81	1.8	250	10
15	33000	2.14	4720	7.50	16500	18	6/8	0.35	14	1.5	5	0.32	0.7	250	10
15	33000	2.14	4720	7.50	16500	18	6/8	0.35	14	3	10	0.64	1.4	250	10
15	33000	2.14	4720	7.50	16500	18	6/8	0.35	14	6	20	1.28	2.8	250	10
25	55000	3.57	7870	12.5	27500	26	1	0.50	20	3	10	1.10	2.4	250	10
25	55000	3.57	7870	12.5	27500	26	1	0.50	20	6	20	2.20	4.9	250	10
25	55000	3.57	7870	12.5	27500	26	1	0.50	20	10	33	3.76	8.1	250	10
45	99000	6.43	14200	22.5	49500	34	1 3/8	0.65	26	3	10	1.82	4.0	250	10
45	99000	6.43	14200	22.5	49500	34	1 3/8	0.65	26	6	20	3.65	8.0	250	10
45	99000	6.43	14200	22.5	49500	34	1 3/8	0.65	26	10	33	6.08	13.4	250	10
60	132000	8.57	18900	30.0	66000	42	1 5/8	0.80	31	3	10	2.69	5.9	250	10
60	132000	8.57	18900	30.0	66000	42	1 5/8	0.80	31	6	20	5.38	11.9	250	10
60	132000	8.57	18900	30.0	66000	42	1 5/8	0.80	31	10	33	8.97	19.8	250	10
75	165000	10.7	23600	37.5	82500	50	2	0.95	37	6	20	3.58	15.8	250	10
75	165000	10.7	23600	37.5	82500	50	2	0.95	37	10	33	7.16	26.3	250	10
75	165000	10.7	23600	37.5	82500	50	2	0.95	37	15	49	11.9	39.5	250	10
100	220000	14.3	31500	50.0	110000	58	2 2/8	1.10	43	6	20	9.85	21.7	400	16
100	220000	14.3	31500	50.0	110000	58	2 2/8	1.10	43	10	33	16.4	36.2	400	16
100	220000	14.3	31500	50.0	110000	58	2 2/8	1.10	43	15	49	24.6	54.3	400	16
120	265000	17.1	37800	60.0	132500	60	2	1.15	39	6	20	10.9	24.0	400	16
120	265000	17.1	37800	60.0	132500	60	2	1.15	39	10	33	18.1	40.0	400	16
120	265000	17.1	37800	60.0	132500	60	2	1.15	39	15	49	27.2	60.0	400	16
150	330000	21.4	47200	75.0	165000	62	2 4/8	1.20	47	6	20	14.5	32.0	400	16
150	330000	21.4	47200	75.0	165000	62	2 4/8	1.20	47	10	33	24.2	53.3	400	16
150	330000	21.4	47200	75.0	165000	62	2 4/8	1.20	47	15	49	36.3	80.0	400	16
200	441000	28.6	63000	100	220500	74	2 7/8	1.40	55	6	20	19.8	43.6	400	16
200	441000	28.6	63000	100	220500	74	2 7/8	1.40	55	10	33	33.0	72.7	400	16
200	441000	28.6	63000	100	220500	74	2 7/8	1.40	55	15	49	49.5	109	400	16
250	551000	35.7	78700	125	275500	84	3 2/8	1.60	63	6	20	26.4	58.2	400	16
250	551000	35.7	78700	125	275500	84	3 2/8	1.60	63	10	33	44.0	96.9	400	16
250	551000	35.7	78700	125	275500	84	3 2/8	1.60	63	15	49	66.0	145	400	16
300	661000	42.9	94500	150	330500	94	3 5/8	1.80	71	6	20	31.7	69.8	400	16
300	661000	42.9	94500	150	330500	94	3 5/8	1.80	71	10	33	52.8	116	400	16
300	661000	42.9	94500	150	330500	94	3 5/8	1.80	71	15	49	79.2	174	400	16

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com



www.marlowropes.com

Disclaimer
Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

Certificate Number 315
ISO 9001

ISO 14001