

Marlow

SOFT SHACKLE - DYNALINE

An all-purpose ready-made fastening option: Marlow's Soft Shackle. A handy kit essential.

Used by sailors, arborists and working-at-height professionals around the world, these light-weight, easy to use shackles are made with Dyneema[®] technical fibre. and are the ultimate in high tech, low weight connections.



Key Specifications:

Material:	Dyneema [®] SK75
Construction:	12 Strand braided
Coating:	'ArmourCoat' PU impregnation
Colours:	Black
Properties:	Very high strength Light weight Low elongation Good UV resistance Excellent Chemical Resistance

PERFORMANCE

ROPE DIAMETER		MASS		AVERAGE SPLICED STRENGTH			MIN SPLICED STRENGTH		
mm	Inch	g	lb	kg	lb	kN	kg	lb	kN
6	7/32	15	0.06	3600	7920	35.3	2880	6336	28.3
8	5/16	40	0.11	7290	16038	71.5	5832	12830	57.2
9	3/8	55	0.13	8786	19330	86.2	7029	15464	69.0
10	13/32	78	0.17	10958	24107	107.5	8766	19285	86.0
11	7/16	100	0.20	13466	29626	132.1	10773	23701	105.7

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com



Certificate Number 315
ISO 9001
ISO 14001

www.marlowropes.com

Disclaimer
Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.