


# Marlow DATASHEET<sup>®</sup>

## VIPER SLING

Factory terminated, CE certified sling made using the durable and heat resistant Viper cord.



### Key Specifications:

<b>Applications:</b>	Prussik
<b>Material:</b>	Vectran/Polyester
<b>Colour:</b>	Blue/natural
<b>Terminations:</b>	Sewn loop Serial numbered, factory CNC sewn terminations for regulatory compliance

### PERFORMANCE

DIAMETER	LENGTH	WEIGHT	MINIMUM BREAK LOAD	AVERAGE BREAK LOAD
mm	cm	g	kN	kN
8	50	49.3	22	27.2
8	60	58.2	22	27.2
8	70	67.2	22	27.2

Marlow Ropes Ltd  
Ropemaker Park  
Hailsham  
East Sussex, BN27 3GU  
England

Marlow Ropes, Inc.  
Cordage Business Park  
Plymouth  
MA 02360  
USA

UK: +44 (0) 1323 444 444  
sales@marlowropes.com  
US: +1 508 830 444  
salesusa@marlowropes.com



Certificate Number 315  
ISO 9001  
ISO 14001

[www.marlowropes.com](http://www.marlowropes.com)

#### Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.