

Marlow

DATASHEET [®]

SUPERYACHT D2 GRAND PRIX



APPLICATIONS:

Excellent all round rope for most on-board applications. Superyacht D2 Grand Prix offers additional abrasion and heat resistance over standard polyester covers. As with Superyacht D2, the rope is strong and flexible making it ideal for most applications.

MATERIAL

CORE:

Dyneema SK78 or SK99. Dyneema SK99 offers approximately 20% strength improvement over standard SK78 whilst maintaining similar creep properties.

CONSTRUCTION

CORE:

12 Strand pre-stretched Dyneema

COVER:

24 Plait Technora / Polyester blend, cover available in custom colours to order

COATING:

ArmourCoat

EXTRAS:

Customised length and colours for a bespoke finish. Available with machine finished splices for additional security and aesthetics.

PERFORMANCE

DIAMETER	WEIGHT	BREAK LOAD 78	BREAK LOAD 99
mm	kg/100m	t	t
12	9.29	6.94	8.26
14	11.7	9.27	11.0
16	16.6	12.8	15.2
18	18.5	15.9	16.4
20	23.7	18.4	21.4
22	29.8	21.1	24.5
24	38.3	25.2	29.2
28	47.8	33.5	38.9
30	54.9	38.8	46.2
32	69.1	41.0	48.8

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

www.marlowropes.com
UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 444
salesusa@marlowropes.com

Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

MA-DA-111 | ISSUE NO.2



Certification Number 315

ISO 9001